DECLARATION of PERFORMANCE.

Ref. no.: YT-16.

1. Product name: 18 mm Forestia P7 Elite

22 mm Forestia P7 Elite

2. Product type: Forestia P7 Elite: Particleboard type: NS-EN 312 P7.

3. Intended use: Load bearing boards for for use in humid conditions.

4. Manufacturer: Forestia AS, 2435 Braskereidfoss, Norway.

5. System of attestation of conformity: System 2+

6. Harmonized standard: NS-EN 13986:2004+A1:2015

Accredited laboratorium: Norsk Treteknisk Institutt, identification no. 1070.

7. Declared performance:

| Essential characteristics: Performa | | | Harmonized technical specification: |
|---|----------------------|---------------|-------------------------------------|
| | 18mm P7 Elite | 22mm P7 Elite | |
| Bending strength | 20 MPa | 18,5 MPa | |
| Modulus of elasticity | 3100 MPa | 2900 MPa | |
| Internal bond | 0,70 MPa | 0,65 MPa | |
| Thickness swelling | ≤10 % | ≤10 % | |
| Moisture resistance after cyclic test: | | | NS-EN |
| - Thickness swelling | | | 13986:2004 |
| - Internal bond | | | +A1:2015 |
| Reaction to fire: | D _{FL} - s1 | | |
| Airborne sound insulation | NPD | | |
| Sound absorption, frequency 250-500 Hz | 0,10 | | |
| " " frequency 1000-2000 Hz | 0,25 | | |
| Water vapor permeability µ, wet / dry cup | 15 / 50 | | |
| Thermal conductivity, W/(m K) | 0,15 | | |
| Biological durability | NPD | | |
| Content of pentachlorophenol (PCP) | <5 ppm | | |
| Formaldehyde potential | Class E1 | | |

NPD = No performance declared

8. The performance of the product identified in points no. 1 and 2 are in conformity with the declared performance in point no. 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point no. 4.

Signed for and on behalf of Forestia AS by:

Vegard Grønnerud, Quality Manager

Name Function.

Braskereidfoss, 27.08.2021

Signature